

4 INCH VALVE BOX WITH A 6 INCH BELL

- The slip-type design protects the service from downward pressure. The box absorbs the pressure from above. If all the downward adjustment is used and additional pressure causes the box to collapse further, the bell area will collapse before damaging the pipe. This is a SAFE installation.
- Meets DOT requirement 192.181; "If the valve is installed in a buried box, the box must be installed so as to avoid transmitting external loads to the main."
- Easily adjusts to grade level. No need to dig when grade changes. Just step-on it to push down or pry it up.
- A full throat/unobstructed upper tube, allows more room to operate the key.
- Made from SUPERIOR GRADE ABS plastic. It's long lasting and won't rust, rot or corrode.
- The box has a 4" upper tube and a 6" bell area.
- Fits up to 2" plastic valves. The closed bell gives flexibility for use on many steel valves.
- Use with any compatible Handley valve support for the ideal installation.
- 1 ½" cast iron flange standard for off-road installations.
- 5" cast iron heavy duty flange is standard for in-road installations.
- Choose from locking or drop-in lids marked GAS, WATER, SEWER, TEST, available with or without vent holes.
- Locking lids are one piece, no parts to be lost.
- 1½" stackable risers, that utilize the same lid, are available when the road is repaved.
- Extensions are available.
- Tracer wire holes can be provided upon request.
- Customized lids are available for an additional charge.
- Use with a Handley valve support for the ideal installation.



This page is intentionally blank to accommodate dual sided printing.



HOW TO ORDER SUPERIOR GRADE 4" VALVE BOXES WITH A 6" BELL

Choose from the following categories to build the valve box best suited to your personal needs. Many options are available so please look this over closely, we don't want you to miss a thing!

ONE = LID LETTERING G = Gas S = Sewer W = Water	TWO = BOX SIZE 4 = 4"	THREE = BOX TYPE V = Valve Box H = Heavy Duty Box	FOUR = ARCH A = Yes N = No
FIVE = ADJUSTABLE RANGE (Measured from top of the box to the bottom of the box. Make your selection from the group that matches your Box Type for Category Three.)			
VALVE BOXES 2 = 24" - 30" 3 = 30" - 42" 4 = 42" - 54" 5 = 54" - 66"		HEAVY DUTY BOXES 2 = 26" - 32" 3 = 32" - 44" 4 = 44" - 56" 5 = 56" - 68"	
SIX = LID TYPE (Locking Lid is Standard) N = Non-Locking			



SEVEN = SUPPORT SYSTEM MODIFICATION

If you are using a support with your Valve Box, one of the codes below is required:

Consult the **HANDLEY VALVE AND BOX SUPPORT** page for additional options or if you require a **BELL PLATE VALVE BOX** please, refer to that page.

CODES VALVE APPLICATION

- 05 = 2" Full-Port Kerotest Polyball Valve
- 05 = 2" Full-Port Lyall-Polytec Ball Valve
- 05 = 2" Full-Port Nordstrom Poly Ball Valve
- 05 = 3" Reduced-Port Kerotest Polyball Valve
- 05 = 3" Reduced-Port Nordstrom Poly Ball Valve
- 05 = 3" Standard-Port Lyall-Polytec Ball Valve
- 08 = 2", 3" Kerotest Poly Butterfly Valves
- 11 = 2" Dresser GTO-Coated & Uncoated Valve
- 24 = 2" Reduced-Port Nordstrom Poly II Ball Valve
- 26 = 2" Handley Plastic Ball Valve
- 33 = 2" Perfection Modified Poly Ball Valve (new) - (see VV25)
- 41 = 1 ¼", 1 ½" Full-Port Kerotest Polyball Valves
- 41 = 2" Reduced-Port Kerotest Polyball Valve
- 42 = 2" Balon Steel Valve

EIGHT = LID COLOR

(Silver is Standard)

A = Yellow

B = Blue

J = Black

NINE = VENT HOLE

C = One 3/8" Vent Hole

TEN = MAGNET

(One Magnet Located in the Flange is Standard)

D = No Magnet (Heavy Duty Boxes are not supplied with a magnet.)

FOR OTHER OPTIONS OR VARIATIONS, PLEASE CONSULT THE FACTORY.

