

6 INCH VALVE BOX WITH A 9 INCH BELL

- The slip-type design protects the service from downward pressure. The box absorbs the pressure from above.
- Meets DOT requirement 192.181; "If the valve is installed in a buried box, the box must be installed so as to avoid transmitting external loads to the main."
- Easily adjusts to grade level. No need to dig when grade changes, just step-on it to push down, or pry it up.
- A full throat/unobstructed upper tube, allows more room to operate the key.
- Made from SUPERIOR GRADE ABS plastic. It's long lasting and won't rust, rot or corrode.
- Light weight and easy to handle.
- 6" I.D. upper tube with a 9" I.D. bell.
- Fits up to 4" plastic valves. The closed bell gives flexibility for use on many steel valves.
- Molded with 2¾", 4" and 6" cut away arches for use with any compatible valve.
- Use with any compatible Handley valve support for the ideal installation.
- Single or multi-slotting is available for use with compatible Handley valve supports.
- 1½" cast iron flange is standard for off-road installations.
- 5" cast iron heavy-duty flange is available for in road installations.
- Choose from locking or drop-in lids marked GAS, WATER, or SEWER.
- Lids are available with or without vent holes.
- 1½" stackable risers, that utilize the same lid, are available when the road is repaved.
- Extensions available.
- Tracer wire holes can be provided upon request.
- Customized lids are available for an additional charge.



This page is intentionally blank to accommodate dual sided printing.



HANDLEY INDUSTRIES, INC.

HOW TO ORDER SUPERIOR GRADE 6" VALVE BOXES WITH A 9" BELL

Choose from the following categories to build the valve box best suited to your personal needs. Many options are available so please look this over closely, we don't want you to miss a thing!

ONE = LID LETTERING G = Gas S = Sewer W = Water	TWO = BOX SIZE 6 = 6"	THREE = BOX TYPE V = Valve Box H = Heavy Duty Box	FOUR = ARCH A = Yes N = No
FIVE = LOWER TUBE DESIGN B = 9" Bell			
SIX = ADJUSTABLE RANGE (Measured from top of the box to the bottom of the box. Make your selection from the group that matches your Box Type for Category Three.)			
VALVE BOXES 2 = 24" - 30" 3 = 29" - 42" 4 = 37" - 54" 5 = 41" - 66"		HEAVY DUTY BOXES 2 = 26" - 32" 3 = 31" - 44" 4 = 39" - 56" 5 = 43" - 68"	
SEVEN = LID TYPE (Locking Lid is Standard) N = Non-Locking			



EIGHT = SUPPORT SYSTEM MODIFICATION

If you are using a support with your Valve Box, one of the codes below is required:

Consult the **HANDLEY VALVE AND BOX SUPPORT** page for additional options or if you require a **BELL PLATE VALVE BOX** please, refer to that page.

CODES	VALVE APPLICATION
06 =	3" Full-Port Kerotest Polyball Valve
06 =	3" Full-Port Lyall-Polytec Ball Valve
06 =	3" Full-Port Nordstrom Poly Ball Valve
06 =	4" Reduced-Port Kerotest Polyball Valve
06 =	4" Reduced-Port Nordstrom Poly Ball Valve
06 =	4" Standard-Port Lyall-Polytec Ball Valve
19 =	2" Kerotest Poly Plug Valve
20 =	4" Kerotest Poly Plug Valve
25 =	2" Perfection Plug Valve (old) - (see VV33)
28 =	3" Kerotest Poly Plug Valve
29 =	2" Frialen-Friatec Poly Ball Valve
30 =	3", 4" Frialen-Friatec Poly Ball Valves

NINE = LID COLOR

(Silver is Standard)

A = Yellow

B = Blue

J = Black

TEN = VENT HOLE

C = One 3/8" Vent Hole

ELEVEN = MAGNET

(One Magnet Located in the Flange is Standard)

D = No Magnet (Heavy Duty Boxes are not supplied with a magnet.)

FOR OTHER OPTIONS OR VARIATIONS, PLEASE CONSULT THE FACTORY.

